

CYCLONE™ ULTRA

Model #2734 and #2736 Handheld ULV Sprayer

The Cyclone Ultra with its 2-stage blower and rugged metering valve assures particles under 20 microns regardless of flow rate and viscosity of material. Ideal for pest control work in areas such as hospitals, nursing homes, schools, apartment buildings, restaurants, greenhouses, etc.

No more guesswork. Now you can apply pesticides deodorants, fungicides, duct sealant, disinfectants, miticides, etc. much safer, more efficiently and more economically. The Cyclone can be used in an unlimited variety of indoor/outdoor applications requiring 5-20 micron droplets.

SPECIFICATIONS

Blower:	Continuous duty, 20,000 RPM. with replaceable brushes. Model#: 2734: 110/120V AC, 8.5 Amps, 50/60 Hz. Model#: 2736: 220/240V AC, 4.2 Amps, 50/60 Hz.
Flow Rate:	0-2.4 oz (70 ml./min.) via metering valve
Droplet Size:	5-20 Microns (VMD)
Tank Capacity:	1 gallon (3.8 liters)



CYCLONE™ ULTRA

Model #	Order #	Description
2734	62250-1	Cyclone Ultra 110 Volt
2736	62250-2	Cyclone Ultra 220 Volt
2730	62300	Cyclone Standard 110 Volt
2732	62350	Cyclone Standard 220 Volt



CYCLONE™ STANDARD

Model #2730 and #2732 Handheld ULV Sprayer

The ultra precision metering valve assures particles under 20 microns regardless of flow rate and viscosity of material. Ideal for pest control work in areas such as hospitals, nursing homes, schools, apartment buildings, restaurants, greenhouses, etc.

SPECIFICATIONS

Input Power:	110/120 V AC, 8.5 amps, 50/60 Hz (model 2730) 210/250 V AC, 4.2 amps, 50/60 Hz (model 2732)
Adjustable:	0-2.4 oz/min.
Flow Rate:	0-70 ml/min.
Particle Size:	5-20 Microns
Tank Capacity:	1 gallon (3.8 liters)



CYCLONE™ STANDARD